

THERE'S A REASON THEY — call it "building" — A REPUTATION.



Tampuise .
Paslode ?
30













TABLE OF CONTENTS

Tools at a Glance	P 4
IM32XP Cordless Impulse XP Framing Nailer	P 8
CFN325IM Cordless Impulse XP Framing Nailer	P 9
PowerMaster Plus Framing Nailser	P 11
Compact Framing Nailer	P 12
PowerMaster Plus 4" Framing Nailer	P 13
SCS200 16 Gauge Standard 1/2" Crown Stapler	P 15
WCS200 16 Gauge Wide 15/16" Crown Stapler	P 16
IMLi200 18 Gauge Brad Nailer	P 17
IMLi200 18 Gauge Short Mag Brad Nailer	P 18
IMLi250 16 Gauge Finish Nailer	P 19
16 Gauge Straight Finish Nailer	P 20
18 Gauge Brad Nailer	P 22
18 Gauge Brad Nailer/Stapler	P 23
18 Gauge Narrow Soffit Stapler	P 25
18 Gauge Narrow Crown Finisher Stapler	P 26
US-100 Upholstery/Craft Stapler	P 27
HP-100 Headless Pin Nailer	P 28
Positive Placement Tool PF250S	P 29
FloorMaster Plus™	P 30
FloorMaster Pro™	P 31
Miscellaneous Fasteners	P 32

TOOL

DESCRIPTION

APPLICATIONS



(see page P 8 for more details)

CORDLESS IMPULSE XP 30°FRAMING NAILER

Drive 1200 nails per fuel cell Drive 9000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.

PART #: 905800 Weight: 7.2 lbs Height: 14-1/2" Length: 12" Nail Capacity: 40

Range: 2" - 3-1/4" Shank: .113 - .131

FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS

DESIGNED FOR: FRAMERS & RENOVATORS



(see page P 9 for more details)

CORDLESS IMPULSE XP **30°FRAMING NAILER**

Drive up to 1200 nails per fuel cell Drive up to 9000 nails per battery charge Faster Nail loading with bypass follower **Tool-free Adjustable Depth of Drive Longer Fan Run Time** 2 sided rubber grip to provide added

PART #: 906450

comfort and control

Weight: 7.2 lbs Height: 14-1/2" Length: 12" Width: 4"

Nail Capacity: 1 strip Range: 2" - 3-1/4" Shank: .113 - .131

Speed: 3 nails per second

FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS

DESIGNED FOR: FRAMERS & RENOVATORS



(see page P 11 for more details)

F350-S POWER MASTER+™

Durable construction requires less maintenance.

Proven performer for tough job site work with less jams or misfires Powerful. Enduring. Reliable.

PART #: 501000 Weight: 8.4 lbs Height: 13-3/10"

Length: 18"

Nail Capacity: (2 strips) 84 Range: 2" - 3-1/2" Shank: .113 - .131

FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS

DESIGNED FOR: PROFESSIONAL FRAMERS



F325R COMPACT FRAMER™

Lightest-framing nailer ever (Only 5.9 lbs) Smallest Framer Ever (Only 12' long) **Remodel interiors easier** Compact. Lightweight

PART #: 513000 Weight: 5.9 lbs Height: 12-9/10" Length: 12-3/10" Range: 2" - 3-1/4" Shank: .113 - .131

Magagine Capacity: 44

FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS

DESIGNED FOR: PROFESSIONAL RENOVATORS



PSN100.1 – 4" FRAMING NAILER 30°

Designed to drive 4" nails Powerful to drive into engineered lumber

Powerful. Fast. Durable.

502900 PART #:

Weight: 8.9 lbs Height: 14-1/2" Length: 19" Nail Capacity: 84 Range: 2" - 4"

Shank: .113 - .131

LSL, LVL, PSL, AND OSB, **ENGINEERED LUMER** FOR FRAMING

DESIGNED FOR: PROFESSIONAL FRAMERS

		TOOL	DESCRIPTION	APPLICATIONS
APLERS	Prodety	SCS200 16GA. STANDARD 1/2" CROWN STAPLER Heavy-duty all metal magazine design for increased durability	Weight: 5.6 lbs Height: 11.7" Length: 15.1" Staple Capacity: 150 Range: 3/4" — 2" Staple Type: 1/2" crown	ROOF DECKING, SOFFITS AND FASCIA BOARDS, SHEATHING
ST	(see page P 15 for more details)	PART #: 515700		
FRAMING STAPLERS	Protor	WCS200 16GA. WIDE 15/16" CROWN STAPLER Drives staples flush in all materials	Weight: 5.9 lbs Height: 11.7" Length: 15.1" Staple Capacity: 150 Range: 3/4" — 2" Staple Type: 15/16" Crown	SOFFITS AND FASCIA BOARDS, SUBFLOOR, SHEATHING, CRATES AND PALLETS
	(see page P 16 for more details)	PART #: 515800		
	Probab	IMLi200 — 18GA. BRAD NAILER Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.	Weight: 4.5 lbs Height: 11-1/2" Length: 11" Nail Capacity: 100 Range: 3/4" - 2" Shank: 18 Gauge	CROWN, BASEBOARD MOULDINGS, PANELLING AND CARPENTRY
S	(see page P 17 for more details)	PART #: 903700		
CORDLESS TRIM NAILERS	(see page P 18 for more details)	IMLI200 18 GA. SHORT MAG BRAD NAILER Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced. PART #: 918150	Weight: 4.25 lbs Height: 11-1/2" Length: 11" Nail Capacity: 70 Range: 5/8" — 2" Shank: 18 Gauge	CROWN, BASEBOARD MOULDINGS, PANELLING AND CARPENTRY
OR	(see page r 16 for infore details)	PART #: 918150		
9		IMLi250 16GA. STRAIGHT FINISH NAILER Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.	Weight: 4.6 lbs Height: 11-3/4" Length: 10-1/2" Nail Capacity: 100 Range: 1-1/4" — 2-1/2" Shank: 16 ga. Straight	DOOR AND WINDOW TRIM, CASING, CROWN AND BASEBOARD MOULDING

(see page P 19 for more details)

PART #:

903800

DESCRIPTION TOOL APPLICATIONS



T250S F16P - 16GA. **STRAIGHT FINISH NAILER**

Best in class ergonomics Reliable and Durable Low Maintenance

Weight: 3.90 lbs Height: 11.6" Length: 12.3"

Nail Capacity: 100 (2 strips)

Range: 1" - 2-1/2" Nail Type: 16 Ga. (Smooth/Galvanized)

RESIDENTIAL: WINDOW AND DOOR TRIM/FINISH APPLICATIONS, CARPENTRY, AND PANELLING

(see page P 20 for more details) PART #:



P18-200 18 GA. **BRAD NAILER**

Lightweight and well balanced No mar tip Easy to access corners

515500

Weight: 2.9 lbs. Height: 9-1/2" Length: 10-1/4" Nail Capacity: 100 Range: 5/8" - 2"

Nail Type: 18 ga. – Smooth, Galvanized

Type: 18 ga.

WINDOWS, DOORS, **FURNITURE, TRIM APPLICATIONS**

(see page P 22 for more details)

PART #: P18-200



(see page P 23 for more details)

P18-FS200 18 GA. **BRAD NAILER/STAPLER**

Lightweight and well balanced No mar tip Easy to access corners

PART #: P18-FS200 Weight: 2.9 lbs. Height: 9-1/2" Length: 10-1/4" Nail Capacity: 100

Range: 5/8" – 2" brad nails and 5/8" - 1-1/2" staples (3/16" crown)

Type: 18 ga. & 3/16

WINDOWS, DOORS, FURNITURE, TRIM **APPLICATIONS**



(see page P 25 for more details)

N18-125 - 1-1/4" **NARROW SOFFIT STAPLER**

Specifically designed for soffit installation with long narrow nosepiece for tight spots.

Weight: 2.5 lbs. Height: 9" Length: 9-1/4" Staple Capacity: 100 Range: 3/4" - 1 1/4" Staple Type: 3/16" crown

GSN18

GSN18

TRIM/FINISH, PLYWOOD, SOFFITS/FACIAS, UNDERLAYMENT **APPLICATIONS**

PART #:

N18-125



(see page P 26 for more details)

N18 150 - 1-1/2" **NARROW CROWN FINISH STAPLER**

Heavy Duty for long life 4000 Shots per batt. charge

PART #: N18-150 Weight: 2.8 lbs. Height: 9-3/4" Length: 11-1/2" Staple Capacity: 100 Range: 3/4" - 1 1/2" Staple Type: 3/16" crown

SOFFITS/FASCIAS, UNDERLAYMENT **APPLICATIONS**

TRIM/FINISH, PLYWOOD,



		TOOL	DESCRIPTION	APPLICATIONS
NING STAPLERS		US-100 — UPHOLSTERY/ CRAFT STAPLER Easy load magazine 5 Staples/second	Weight: 2.00 lbs. Height: 9-1/2" Length: 12-1/2" Staple Capacity: 100 Range: 3/8" — 9/16" Staple Type: 22 ga. Upholstery	UPHOLSTERY, CRAFTS, LIGHT PANELING AND HOME PROJECT APPLICATIONS
	(see page P 27 for more details)	PART #: US-100		
LITE GAUGE FASTENING STAPLERS		23GA HEADLESS PIN NAILER Lightweight and compact No mar tip and nail lock out	Weight: 1.20 lbs. Height: 9-1/4" Length: 7-3/4" Staple Capacity: 100 Range: 1/2" — 1-1/2" Staple Type: 23 ga.	FINE WOODWORKING AND TRIM WORK
	(see page P 28 for more details)	PART #: HP100		
JOIST HANGERS	(see page P 29 for more details)	2.5" POSITIVE PLACEMENT® METAL CONNECTOR NAILER PF250S Dependable, Lightweight, Compact and Accurate PART #: 511800	Weight: 7.8 IBS Height: 14" Length:17.4" Nail Capacity: 55-60 Nails (2 strip Nail Range: .131" to .162" (Shar Magazine Angle: 30 Degrees Nail Type: 1-1/2" to 2-1/2" Positiv Placement Hanger Nails — Brite a Air req: 80-120 PSI	nk) PROFESSIONAL FRAMERS ve
NG		FLOORMASTER PLUS™ 2 IN 1 FLOORING NAILER/ STAPLER Drives staples and cleats to meet flooring manufacturers fastening specifications	Weight: 10.4 lbs Height: 18" Length: 16" Flooring Fasteners: 15ga staples & 16ga L-cleats Fastener Lengths: 2", 1-3/4, 1-1/2"	3/4" HARDWOOD FLOORING
- -	(see page P 30 for more details)	PART #: F2N1-200		
FLOORING		FLOORMASTER PRO™ NAILER/STAPLER 2 IN 1 COMBO Professional Grade Durability & Performance	Weight: 11 lbs Height: 21-5/8" Length: 18" Flooring Fasteners: 15-1/2ga staples & 16ga L-Cleats Fastener Lengths: 2", 1-3/4, 1-1/2"	3/4" SOLID AND ENGINEERED FLOORING

(see page P 31 for more details)

PART #:

FNS-200



IM325XP Cordless Impulse XP Framing Nailer

Portable freedom on the jobsite without hoses or compressors



INCLUDES

Cordless Li-ion Framing Nailer, Model IM325XP Rechargeable 7.4V Li-ion battery

Li-ion battery charger

Rugged carrying case

Owner's manual

Safety glasses

5/32" Hex Wrench

DESCRIPTION/SUGGESTED SPECIFICATIONS

Cordless Impulse XP Framing Nailer—

IT'S MORE THAN A NAILER, IT'S A NAILING SYSTEM THAT GETS THE JOB DONE RIGHT.

The Paslode Lithium Ion cordless Impulse nailer has provided framers and renovators the ability to wood frame without air hoses for over 25 years. New Li-ion battery technology drives 50% more nails per charge. 2-times faster charge time; 2 minute quick charge drives up to 200 nails. Tool free depth of drive adjustment, non slip grip, dual position utility hook, sequential operation triggers.

LIGHTWEIGHT



OUICK LOADING



EASY ACCESS



ADVANTAGES

- Portable, freedom on the jobsite without hoses or compressors
- Heavy-duty rafter/belt hook for taking jobsite abuse
- Non-slip grip provides comfort and reduces hand fatigue
- Tool free depth-of-drive nail adjustment changes nail depth in an instant even while wearing gloves
- Nail lockout feature prevents blank driving
- Compact size fits between 16" o.c. studs, joists and roof trusses
- Li-ion battery provides 50% longer run time (up to 9,000 nails per charge) than NiCd battery
- 1-hour Full Charge; 2-minute Quick Charge for Up to 200 shots
- Lightweight 7.2 lbs. including battery for better comfort and control
- Works in cold temperature down to -15°C

SPECIFICATIONS

 Part No. 905800
 Range: 2" - 3-1/4"

 Weight: 7.2 lbs
 Shank: .113 - .131

 Height: 14-1/2"
 Nail Angle: 30°

Length: 12" Fuel Type: Spare Framing Fuel

Width: 4" Nails per Fuel Cell: Approximately 1200

Speed: 2-3 nails per second Fuel life: 21 months from date of manufacture

Nail Capacity: 40 Battery Life: 9000 nails per charge

ONE-YEAR LIMITED WARRANTY A one-year warranty will apply to all parts, except those listed below as normal wearing parts, or parts-which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all molded nylon parts:

• Motor Housing, Cap and Grille

• Trigger

• Handle Halves and Actuator

• Magazine Parts

90-DAY LIMITED WARRANTY A 90-day warranty applies to the following parts, which are considered normal wearing parts:

• Bumper

• O-Rings

• Driver Blades

• Seal Rings



CFN325IM Cordless Impulse XP Framing Nailer

Fuel powered performance to keep your jobsties going



INCLUDES

Cordless Li-ion Framing Nailer, Model CFN325IM Rechargeable 7.4V Li-ion battery

Li-ion battery charger

Rugged carrying case

Owner's manual

OWINCE 3 III diluc

Safety glasses

5/32" Hex Wrench

DESCRIPTION/SUGGESTED SPECIFICATIONS

Cordless Impulse XP Framing Nailer—

IT'S MORE THAN A NAILER, IT'S A NAILING SYSTEM THAT GETS THE JOB DONE RIGHT.

The Paslode Lithium Ion cordless Impulse nailer has provided framers and renovators the ability to wood frame without air hoses for over 30 years. The Li-ion battery technology drives up to 200 nails and 2 minutes quick drive. Tool free adjustable depth of drive adjustment, 2 sided rubber grip to provide added comfort and control and a rear load magazine allowing for faster nail loading with bypass follower.

LIGHTWEIGHT



OUICK LOADING



EASY ACCESS



ADVANTAGES

- REAR LOAD MAGAZINE Faster nail loading with Bypass Follower just load nails and pull
- TOOL-FREE ADJUSTABLE DEPTH OF DRIVE
- 2-SIDED RUBBER GRIP Added comfort and control with improved ergonomics and maneuverability
- LONGER FAN RUN TIME Improved cooling provides greater productivity
- Li-ion battery provides 50% longer run time (drives up to 9,000 nails per charge) than NiCd battery
- 1-hour Full Charge; 2-minute Quick Charge for Up to 200 shots
- Lightweight 7.2 lbs. including battery for better comfort and control
- Works in cold temperature down to -15°C

SPECIFICATIONS

Part No. 906450

Weight: 7.2 lbs Height: 14-1/2"

Length: 12"

Width: 4"

Speed: 3 nails per second

Nail Capacity: 1 strip

Range: 2" — 3-1/4"

Shank: .113 – .131

Nail Angle: 30°

Fuel Type: Spare Framing Fuel

Nails per Fuel Cell: Approximately 1200

Fuel life: 21 months from date of manufacture

Battery Life: 9000 nails per charge

ONE-YEAR LIMITED WARRANTY A one-year warranty will apply to all parts, except those listed below as normal wearing parts, or parts-which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all molded nylon parts: • Motor Housing, Cap and Grille • Trigger • Handle Halves and Actuator • Magazine Parts 90-DAY LIMITED WARRANTY A 90-day warranty applies to the following parts, which are considered normal wearing parts: • Bumper • O-Rings • Driver Blades • Seal Rings



Cordless Impulse XP Framing Nailer

SELECTION CHART

Pro-S	trip Ro	unDri	ve Nail	S								
LENGTH	SHANK DIAMETER	SHANK TYPE	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER PACK	QUANTITY PER MASTER	QUANTITY PER SKID				
COATING	COATING TYPE: BRITE											
2"	0.113	Smooth	Roundrive	Brite	097385	6,500	1	80				
2"	0.113	Ring	Roundrive	Brite	650273	5,500	1	80				
2-3/8"	0.113	Smooth	Roundrive	Brite	50238	5 Strips	10	-				
2-3/8"	0.113	Smooth	Roundrive	Brite	404238	1,000	4	-				
2-3/8"	0.113	Smooth	Roundrive	Brite	097394	5,000	1	96				
2-3/8"	0.113	Ring	Roundrive	Brite	097397	5,000	1	96				
3"	0.120	Smooth	Roundrive	Brite	097971	3,000	1	96				
3"	0.120	Ring	Roundrive	Brite	097973	3,000	1	96				
3-1/4"	0.120	Smooth	Roundrive	Brite	50314	5 Strips	1	125				
3-1/4"	0.120	Smooth	Roundrive	Brite	404314	1,000	4	-				
3-1/4"	0.120	Smooth	Roundrive	Brite	404058	3,000	1	96				
3-1/4"	0.131	Smooth	Roundrive	Brite	650839	2,500	1	96				
3-1/4"	0.131	Ring	Roundrive	Brite	097978	2,500	1	96				
3-1/2"	0.120	Smooth	Roundrive	Brite	404855	2,500	1	96				
3-1/2"	0.131	Smooth	Roundrive	Brite	097987	2,500	1	96				
4"	0.131	Smooth	Roundrive	Brite	2X0788 *	2,500	1	96				
COATING	TYPE: HOT DIE	PPED										
2"	0.113	Ring	Offset Oval	Hot Dipped	403389	2,500	1	150				
2-3/8"	0.113	Ring	Offset Oval	Hot Dipped	404856	2,500	1	150				
3"	0.120	Ring	Offset Oval	Hot Dipped	404857	1,500	1	150				

Pro-Strip RounDrive Fuel/Nail Packs

Ring

Ring

Offset Oval

Offset Oval

Ī	LENGTH	SHANK	SHANK TYPE	HEAD STYLE	COATING	PRODUCT	NAILS PER	FUEL CELLS
L		DIAMETER				NUMBER	PACK	PER PACK
	2-3/8"	0.113	Smooth	Roundrive	Brite	1238FN	1,000	1
	2-3/8"	0.113	Smooth	Roundrive	Brite	3238FN	3,000	3
	3"	0.120	Smooth	Roundrive	Brite	3300FN	3,000	3
	3-1/4"	0.120	Smooth	Roundrive	Brite	1325FN	1,000	1
	3-1/4"	0.120	Smooth	Roundrive	Brite	3325FN	3,000	3

Hot Dipped

Hot Dipped

50314G

404858

5 Strips

1,500

6

1

150

See Page P 14 for additional framing nails that work with this tool.

- 1. ICC ESR-1539 applies to all of our framing nails except for Part#650839 which falls under ICC ESR-3072.
- 2. HDG Nails are approved to be used in ACQ & MCQ treated lumber as per ASTM A641 & IRC R317.3
- 3. Paslode Nails meet ASTM 1667 standards
- * ICC ESR Report does not include this product.

APPLICATIONS



Framing
Joists and rafters
Soffits
Stairs
Sheathing
Crating
Fences and decks

TOOL ACCESSORIES







Part No. 902654C Li Ion Battery



Part No. 902667C Lithium Battery Charger



Part No. 901252 Cordless No mar tip



Part No. 401482 Impulse Oil



Part No. 219086 Degreaser

3 1/4"

3-1/4"

0.120

0.120



PF-350S PowerMaster Plus Framing Nailer

Durability, Balance and Versatility for all jobs



INCLUDES

PowerMaster™ Plus Pneumatic Framing Nailer

Bump fire trigger

Hex wrench (on tool)

Safety glasses

Owner's manual

TOOL ACCESSORIES







Part No. 219090

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus Framing Nailer—

DESIGNED FOR PROFESSIONAL FRAMERS

Heavy-duty jobs require a heavy-duty nailer. That's why the pros turn to the proven performance, durability and driving power, only a Paslode pneumatic framing nailer can provide. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.

POWERFUL



FAST



DEPENDABLE



ADVANTAGES

- Frame full walls faster. Heavy duty power.
- Reliable performance that saves time with less maintenance.
 - Durable construction requires less maintenance.
 - Proven performer for tough job site work with less jams or misfires
 - Compact size fits between 16" o.c. studs, joists and rafters.
- Soft grip handle for comfort
- Bolt-on end plug for easier service
- Depth of drive on the tool rather than the compressor saves time and energy
- Rafter hook, moves out of the way when not in need
- Adjustable air deflector cap

APPLICATIONS



Framing

Sheathing

Joists and rafters

Crating

Soffits

Stairs

Fences and decks

SPECIFICATIONS

Part No. 501000

Weight: 8.4 lbs

Height: 13-3/10"

Length: 18"

Speed: 12 nails per second*, sequential or selectable operation

Nail Capacity: 2 strips (up to 84)

Nail Range: 2" – 3.5" in length, .113" – .131" shank diameters

Nail Angle: 30°

Nail Type: Paslode RounDrive® Offset Full Head

Air Req./100p.s.i. (6.9 bar): .082/cycle

Op. Pres. p.s.i (bar): 80 - 120 (5.5 - 8.3)

Warranty: 90-day limited on wear parts, 1-year limited on magazine parts, 5-year limited on housing and cap parts



F325R Compact Framing

Lightest weight framer ever



FRAMING NAILS SELECTION CHART

INCLUDES

Compact 30° Framing Nailer Safety glasses

Owner's manual

OOL ACCESSORIES





Pneumatic Oil



Part No. 219090

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

Compact Framing Nailer—

DESIGNED FOR RENOVATORS

With this nailing system, you'll have any interior remodeling job done in no time. Get the access and maneuverability you need in tight spaces with this lightweight yet powerful pneumatic nailing system. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.

PROFESSIONAL



LIGHTWEIGHT



EASY ACCESS



ADVANTAGES

- Remodel interiors easier. Lightest weight framer ever.
 - Remodel Interiors Fasier
 - First pneumatic nailer made especially with remodeler's needs in mind
 - Fits easily into the tightest spaces such as between 16" o.c. studs
- Great maneuverability to work comfortably overhead
- Lightest-framing nailer ever made: 5.9 lbs
- Quick 2-step nail strip reload
- Soft grip handle for comfort
- Works in bump mode for speed on jobsite

APPLICATIONS



Framing

Joists and rafters

Soffits **Stairs**

Sheathing

Crating

Fences and decks

SPECIFICATIONS

Part No. 513000

Weight: 5.9 Pounds

Height: 12-9/10"

Width: 4-3/10"

Length: 12-3/10"

Fastener Range: 2" - 3 1/4"

Shank: .113 - .131

Magazine Capacity: 44

Op. Pres. p.s.i (bar): 90 - 120



PowerMaster Framing Nailer

Proven durability and reliability



INCLUDES

PowerMaster Plus 4" Framing Nailer

Safety glasses

Owner's manual

TOOL ACCESSORIES





Part No. 403720

Pneumatic Oil



Part No. 219090

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus 4"—

DESIGNED FOR TIMBER FRAMERS

The F400S is the PowerMaster Plus framing nailer with an extended power and driver blade for 4" applications.



FAST

DEPENDABLE

ADVANTAGES

- PowerMaster Plus Design Proven durability and reliability
- Versatile Drives a variety of nails from 1-1/2" to 4" in length.
- Ergonomic Design Centre of gravity is closer to the trigger, providing better balance.
- Durable And Reliable Rugged design will stand up to the demands of the job in any kind of weather.

PPLICATIONS



LSL, LVL, PSL, and OSB

Wall Sheathing

Framing

Floor Decking

Roof

SPECIFICATIONS

Part No. 502900

Weight: 8.9 lbs

Height: 14-1/2"

Length: 19"

Nail Capacity: 84

Range: 2" - 4"

Shank: .113 - .131

Back of to tool to Nosepiece: 14.5"

Magazine Angle: 30°

Nail Type: 30° Paper Tape, full head/clipped

OP. Pres. p.s.i. (bar): 80 - 120 (5.5 - 8.3)

Warranty: 90-day limited on wear parts,

6-month limited on magazine parts,

1-year limited on housing and cap parts.

Pneumatic Strip Framing Nailers

SELECTION CHART

Pro-St	Pro-Strip RounDrive Nails										
LENGTH	SHANK DIAMETER	SHANK Type	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER PACK	QI PEI				

LENGTH	SHANK DIAMETER	SHANK TYPE	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER PACK	QUANTITY PER MASTER	QUANTITY PER SKID
COATING TY	PE: BRITE			ſ				
2"	0.113	Smooth	Roundrive	Brite	097385	6,500	1	80
2"	0.113	Ring	Roundrive	Brite	650273	5,500	1	80
2-3/8"	0.113	Smooth	Roundrive	Brite	50238	5 Strips	10	-
2-3/8"	0.113	Smooth	Roundrive	Brite	404238	1,000	4	-
2-3/8"	0.113	Smooth	Roundrive	Brite	097394	5,000	1	96
2-3/8"	0.113	Ring	Roundrive	Brite	097397	5,000	1	96
3"	0.120	Smooth	Roundrive	Brite	097971	3,000	1	96
3"	0.120	Ring	Roundrive	Brite	097973	3,000	1	96
3-1/4"	0.120	Smooth	Roundrive	Brite	50314	5 Strips	1	125
3-1/4"	0.120	Smooth	Roundrive	Brite	404314	1,000	4	-
3-1/4"	0.120	Smooth	Roundrive	Brite	404058	3,000	1	96
3-1/4"	0.131	Smooth	Roundrive	Brite	650839	2,500	1	96
3-1/4"	0.131	Ring	Roundrive	Brite	097978	2,500	1	96
3-1/2"	0.120	Smooth	Roundrive	Brite	404855	2,500	1	96
3-1/2"	0.131	Smooth	Roundrive	Brite	097987	2,500	1	96
4"	0.131	Smooth	Roundrive	Brite	2X0788*	2,500	1	96
COATING TY	PE: HOT DIPPE	D						
2"	0.113	Ring	Offset Oval	Hot Dipped	403389	2,500	1	150
2-3/8"	0.113	Ring	Offset Oval	Hot Dipped	404856	2,500	1	150
3"	0.120	Ring	Offset Oval	Hot Dipped	404857	1,500	1	150
3 1/4"	0.120	Ring	Offset Oval	Hot Dipped	50314G	5 Strips	6	-
3-1/4"	0.120	Ring	Offset Oval	Hot Dipped	404858	1,500	1	150





Also works with Cordless Impulse Framing Nailer (see page P 9)

- 1. ICC ESR-1539 applies to all of our framing nails except for Part#650839 which falls under ICC ESR-3072.
- 2. HDG Nails are approved to be used in ACQ & MCQ treated lumber as per ASTM A641 & IRC R317.3
- 3. Paslode Nails meet ASTM 1667 standards
- * ICC ESR Report does not include this product.

PRO-STRIP ROUNDRIVE NAILS FOR USE WITH



POWERMASTER PLUS



COMPACT FRAMER



POWERMASTER PLUS 4" FRAMER



CORDLESS IMPULSE XP FRAMING NAILER



SCS200 16 Ga. Standard 1/2" Crown Stapler

Heavy-duty all metal magazine design for increased durability



INCLUDES

SCS200 Crown Stapler Pneumatic Lubricating Oil Safety glasses

Owner's manual

TOOL ACCESSORIES







Part No. 219090
Pneumatic Oil w/ Antifreeze

POWERFUL



FAST

DESCRIPTION/SUGGESTED SPECIFICATIONS

staples. this durable stapler will hold up to any jobsite conditions or high volume industrial usage..

SCS200 16Ga. Standard 1/2" Crown Stapler

WITH THE RIGHT STAPLER AND STAPLES, YOU'LL HAVE THE JOB DONE IN NO TIME.

The new Paslode 16ga standard crown stapler is built for professional framers with speed and power that will increase jobsite productivity by allowing you to work quickly, never having to pull out your hammer to finish off

DEPENDABLE



ADVANTAGES

- Lightweight: Only 5.6 lbs
- Staple Capacity: Up to 150 staples
- **Quick-Clear Nose:** For easy jam clearance
- Staple Range: 3/4" 2"
- Quick Release Follower Tab: Makes reloading fast

SELECTION CHART

16 Gauge Standard Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1″	1/2"	Chisel	16	Galvanized	0T5242	16,500
1-1/4"	1/2"	Chisel	16	Galvanized	0T5238	13,500
1-1/2"	1/2"	Chisel	16	Galvanized	0T2695	10,500
1-3/4"	1/2"	Chisel	16	Galvanized	0T2250	9,000
2"	1/2"	Chisel	16	Galvanized	0T2258	7,500

APPLICATIONS



Roof Decking

Soffits and Fascia Boards

Sheathing

SPECIFICATIONS

Part No. 515700

Weight: 5.6 lbs Op. Pres. 80 to 120 p.s.i. (5.5 to 8.3 bars)

Height: 11.7" Staple Length: 3/4" – 2"
Width: 3/4" Staple Diameter: 16 gauge

ONE-YEAR FULL WARRANTY A one-year warranty will apply to all parts, except those which are specifically covered by an extended warranty.

Length: 15.1"

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all housing and cap assembly castings.







WCS200 16 Ga. Wide 15/16" Crown Stapler

Drives staples flush in all materials



INCLUDES

WCS200 Wide 15/16" Crown Stapler

Pneumatic Lubricating Oil

Safety glasses

Owner's manual

TOOL ACCESSORIES







Part No. 219090

Pneumatic Oil Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

WCS200 16Ga. Wide 15/16" Crown Stapler

RELIABLE. DURABLE. POWERFUL.

Tested and proven to reliably hold up to any application on most extreme jobsites. By using Paslode staples, you'll have fewer jams, fewer misfires and faster loading, only a Paslode stapling system can deliver.





DEPENDABLE



ADVANTAGES

- Lightweight: only 5.9 lbs
- Quick-Clear Nose: For easy jam clearance
- Quick Release Follower Tab: Makes reloading fast
- **Staple Capacity**: Up to 150 staples
- **Staple Range:** 3/4" − 2"
- Tool-free Adjustable Depth of Drive: Easily adjust depth for consistency in any material

SELECTION CHART

16 Gauge Wide Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
7/8"	15/16"	Chisel	16	Galvanized	404069	9,000
1-1/2"	15/16"	Chisel	16	Galvanized	0T2855	10,500

APPLICATIONS



Soffits and Fascia Boards

Subfloor

Sheathing

Crates and Pallets

SPECIFICATIONS

Part No. 515800 Length: 15.1"

Weight: 5.9 lbs Op. Pres. 80 to 120 p.s.i. (5.5 to 8.3 bars)

Height: 11.7" Staple Length: 3/4" – 2" Width: 3/4" Staple Diameter: 16 gauge

ONE-YEAR FULL WARRANTY A one-year warranty will apply to all parts, except those which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all housing and cap assembly castings.



IMLi200 18 Gauge Brad Nailer

Lightweight and well balanced



TOOL ACCESSORIES

Part No. 902654C Lithium Ion 7.4v battery
Part No. 902667C Lithium Ion Battery Charger
Part No. 219236 3 Pack of No Mar Tips
Part No. 219086 Degreaser Cleaner
Part No. 401482 Impulse Oil

Universal Trim Fuel Cell (4 pk)

INCLUDES

Part No. 650039

IMLi200 18 Ga Brad Nailer Rugged Carrying Case Rechargeable Battery with Charger

Safety glasses Owner's manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

18 Gauge Brad Nailer—

WE'VE GOT THE FACTS NAILED.

When you need precision in tight spaces, reach for the lightweight Paslode Cordless Finishing Nailing System. It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away

POWERFUL PRECISE PRODUCTIVE PENNIES PER SHOT









ADVANTAGES

- Li-lon for 50% more shots (12,000) per charge
- Quick charge to 80% in 30 minutes
- New battery standby position conserves charge
- New easier depth of drive thumbwheel
- New reversible belt hook
- 8% lighter 4.5 lbs with battery (compared with Ni-Cad battery)

SELECTION CHART

18 Gauge Fuel and Finish Nail Packs

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/2"	0.048	Chisel	18	Galvanized	FFP-118112	1,000
2"	0.048	Chisel	18	Galvanized	FFP-118002	1,000

See Page P 23 for additional finish nails that work with this tool.

APPLICATIONS





Crown and baseboard mouldings

Panelling

Carpentry

SPECIFICATIONS

Part No. 903700

Weight: 4.5 lbs Nail Capacity: 100

Height: 11-1/2" Nail Range: 5/8" — 2"

Length: 11" Nail Type: 18 ga

ONE-YEAR LIMITED WARRANTY A one-year warranty will apply to all parts, except those listed below as normal wearing parts, or parts-which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all molded nylon parts:

• Motor Housing, Cap and Grille

• Handle Halves and Actuator

• Trigger

• Magazine Parts

90-DAY LIMITED WARRANTY A 90-day warranty applies to the following parts, which are considered normal wearing parts:
• Bumper
• Driver Blades
• O-Rings
• Seal Rings



IMLi200 18 Ga. Short Mag Brad Nailer

Made to Fit in Tight Spaces



TOOL ACCESSORIES

Part No. 902654C Lithium Ion 7.4v battery
Part No. 902667C Lithium Ion Battery Charger
Part No. 219236 3 Pack of No Mar Tips
Part No. 219086 Degreaser Cleaner

Part No. 401482 Impulse Oil

art No. 401482 Impulse Of

Part No. 650039 Yellow Trim Fuel Cell (4 pk)

Paslode

INCLUDES

IMLi200 18 Ga Short Mag Brad Nailer

Rugged Carrying Case

Rechargeable Battery with Charger

Safety glasses

Owner's manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

18 Ga. Cordless Li-ion Brad Nailer - 1 Strip

MANEUVERABLE. PRECISE. LIGHTWEIGHT.

The NEW Paslode 18 Ga. Cordless Li-ion Brad Nailer is the ideal nailer for all of your trim projects. This tools has superior access to tight spaces so you are able to fasten in areas that aren't easily accessible. This consistent nailer makes your job easier than ever, driving each nail flush into all types of trim. Finally, weighing 4.25 lbs., this is the lightest Cordless Brad Nailer on the market.

POWERFUL PRECISE PRODUCTIVE PENNIES PER SHOT









ADVANTAGES

- 7.4-volt Li-ion battery drives up to 12,000 s/b nails per charge
- 1-1/2 hour full charge; 2-minute quick charge for up to 200 extra shots
- Battery stand-by position secures battery in off position to conserve battery power
- Reversible belt hook Easily adjusts and keeps both hands free
- Tool free depth of drive is easy to adjust, even with gloves on

SELECTION CHART

18 Gauge Fuel and Finish Nail Packs

LENGTH	SHANK DIAMETER	SHANK Type	GUAGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/2"	0.048	Chisel	18	Galvanized	FFP-118112	1,000
2"	0.048	Chisel	18	Galvanized	FFP-118002	1,000

See Page P 24 for additional finish nails that work with this tool.

APPLICATIONS



Window Castings

Baseboards moldings

Decorative trim

SPECIFICATIONS

Part No. 918150

Weight: 4.25 lbs Nail Range: 5/8" — 2" Height: 11-1/2" Nail Type: 18 ga

Height: 11-1/2" Nail Type: 18 ga Length: 11" Warranty: 1-yea

Length: 11" Warranty: 1-year limited

Nail Capacity:70 For full warranty details, visit

https://paslode.ca/warranty/



IMLi250 16 Gauge Finish Nailer

Lightweight and well balanced



TOOL ACCESSORIES

Part No. 902654C Lithium Ion 7.4v battery
Part No. 902667C Lithium Ion Battery Charger
Part No. 219236 3 Pack of No Mar Tips
Part No. 219086 Degreaser Cleaner
Part No. 401482 Impulse Oil

Universal Trim Fuel Cell (4 pk)

INCLUDES

Part No. 650039

IMli250 16 Ga Straight Finish Nailer

Rugged Carrying Case

Rechargeable Battery with Charger

Safety Glasses

Owner's Manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

16 Gauge Straight Cordless Finish Nailer—

GREAT MANEUVERABILITY.

It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away.

POWERFUL









ADVANTAGES

- Powerful precision Finish right the first time.
- Li-ion Battery Drives up to 12,000 nails per charge
- Lightweight Only 4.6 pounds for added comfort and control
- Use Paslode Universal Trim Fuel Drives approx. 1,000 nails
- Battery Standby Position Conserves battery power
- 1 Hour Rapid Charger 80% charge in 20 min

SELECTION CHART

16 Gauge Fuel and Finish Nail Packs

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1 1/2"	0.063	Chisel	16	Galvanized	FFP-116112	1,000
2"	0.063	Chisel	16	Galvanized	FFP-116002	1,000

See Page P 21 for additional finish nails that work with this tool.

APPLICATIONS



Door and window trim

Casing

Crown and baseboard moulding

SPECIFICATIONS

Part No. 903800

Weight: 4.6 lbs
Nail Capacity: 100
Height: 11-3/4"
Nail Range: 1" - 2-1/2"
Length: 10-1/2"
Nail Type: 16 ga Straight

ONE-YEAR LIMITED WARRANTY A one-year warranty will apply to all parts, except those listed below as normal wearing parts, or parts-which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all molded nylon parts:

• Motor Housing, Cap and Grille • Handle Halves and Actuator • Trigger • Magazine Parts

90-DAY LIMITED WARRANTY A 90-day warranty applies to the following parts, which are considered normal wearing parts: • Bumper • Driver Blades • O-Rings • Seal Rings



T250S F16P 16 Gauge Finish Nailer

Best in Class Ergonomics



DESCRIPTION/SUGGESTED SPECIFICATIONS

T250S F16P - 16 Gauge Finish Nailer—

LIGHTWEIGHT, HIGH PERFORMANCE, LOW MAINTENANCE,

The Paslode 16 Ga. Pneumatic Finish Nailer has a best-in-class design that allows for comfort in all applications. This is a reliable and durable tool you can trust to keep up with you. The oil-free design allows for long term, maintenance-free operation which reduces cleanup time and associated costs.

LIGHTWEIGHT



DEPENDABLE



OIL FREE



ADVANTAGES

- Best in class ergonomics Designed with enhanced features to optimize balance, maximize comfort, reduce fatigue and increase productivity
- Reliability and durability Proven performance that saves you time and can keep up with you
- Low maintenance Oil-free design allows for long term, maintenance-free operation which reduces cleanup time and associated costs

APPLICATIONS



Window and door trim/finish applications

Carpentry

Panelling

INCLUDES

T250S F16P - 16 Gauge Finish Nailer

1/4" air fitting

Rugged Carrying Case

Owner's Manual

Safety Glasses

SPECIFICATIONS

Part No. 515500

Weight: 3.9 lbs

Height: 11.6"

Length: 12.3"

Nail Capacity: 100 (2 strips)

Nail Range: 1" - 2-1/2"

Magazine Angle: Straight Collation

Nail Type: 16 Ga. (Smooth/Galvanized)

Op. Pressure P.S.I (Bar): 80-120 p.s.i

Warranty: 5 Year limited warranty

For full warranty details, visit

https://paslode.ca/warranty/



SELECTION CHART

16			4-6	Ma:L	٩
10	Gaug	e rin	11/11	MUIII	3

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1"	0.063	Chisel	16	Galvanized	095203	5,000
1-1/4"	0.063	Chisel	16	Galvanized	095205	5,000
1-1/2"	0.063	Chisel	16	Galvanized	095257	4,000
1-3/4"	0.063	Chisel	16	Galvanized	095435	2,500
2"	0.063	Chisel	16	Galvanized	095436	2,500
2-1/2"	0.063	Chisel	16	Galvanized	090025	2,500
MULTI	0.063	Chisel	16	Galvanized	116000	2,000
1"	0.063	Chisel	16	Galvanized	116001	1,000
1-1/4"	0.063	Chisel	16	Galvanized	116114	1,000
1-1/2"	0.063	Chisel	16	Galvanized	116112	1,000
1-3/4"	0.063	Chisel	16	Galvanized	116134	1,000
2"	0.063	Chisel	16	Galvanized	116002	1,000
2-1/4"	0.063	Chisel	16	Galvanized	400601	2,500
2-1/2"	0.063	Chisel	16	Galvanized	116025	1,000

- Approved for use in all pressure treated lumber such as ACQ and MCQ
- Polymer coating on nail head reduces staining and streaking by 80% compared to traditional hot dipped galvanized nails
- IRC R319.3 code approved for use in pressure treated lumber in accordance with ASTM A 153



16 GAUGE FINISH NAILS FOR USE WITH







IMLi250 – 16 GAUGE FINISH NAILER

TOOL ACCESSORIES



Part No. 403720 Pneumatic Oil



Part No. 219090
Pneumatic Oil w/
Antifreeze



Part No. 650039 Universal Trim Fuel Cell (4 Pk)



P18-200 18 Gauge Brad Nailer

Jobsite tough all metal housing and magazine



SEE PAGE P 23 FOR 18 GAUGE NAILS SELECTION CHART

INCLUDES

P18-200 18 Gauge Brad Nailer

3 no mar tips

Air fitting

0il

Safety glasses

Allen wrenches

DESCRIPTION/SUGGESTED SPECIFICATIONS

P18-200 18 Gauge Brad Nailer —

BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.

LIGHTWEIGHT



PRECISE



EASY ACCESS



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout

- Quick-release nose
- 360° adjustabler exhaust
- 5/8" to 2" nails

APPLICATIONS

Windows

Doors

Furniture

Trim applications

SPECIFICATIONS

Part No. P18-200

Weight: 2.9 lbs

Height: 9.5" Length: 10.25" Nail Capacity: 100

Nail Range: 5/8" — 2" Magazine Angle: Straight Nail Type: 18 Gauge - Smooth, Galvanized

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts



P18-FS200 18 Gauge Brad Nailer/ Stapler

Paslode driving power with the features contractors demand



SEE PAGE P 25 FOR 18 GA. 1/4" CROWN STAPLES

DESCRIPTION/SUGGESTED SPECIFICATIONS

P18-FS200 18 Gauge Brad Nailer/Stapler —

BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.

LIGHTWEIGHT



PRECISE



EASY ACCESS



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout

- Quick-release nose
- 360° adjustable exhaust
- 5/8" to 2" Nails, 5/8" to 1-1/2" staples

APPLICATIONS

Windows

Doors

Furniture

Trim applications

INCLUDES

P18-FS200 18 Gauge Brad Nailer/Stapler

3 no mar tips

Air fitting

0il

Safety glasses

Allen wrenches

SPECIFICATIONS

Part No. P18-FS200

Weight: 2.9 lbs

Height: 9.5"

Length: 10.25"

Nail Capacity: 100

Nail Range: 5/8" – 2" brad nails and 5/8" - 1-1/2" staples (1/4" crown)

Magazine Angle: Straight

Nail Type: 18 Gauge - Smooth,

Galvanized Nails and 1/4" Crown Staples

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts,

1-year limited on housing and cap parts.

18 Gauge Brad Nailers/Stapler

SELECTION CHART

18 Gauge Finish Nails

LENGTH	SHANK DIAMETER	SHANK Type	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
MULTI	0.048	Chisel	18	Galvanized	118000	2,000
1"	0.048	Chisel	18	Galvanized	118001	1,000
2"	0.048	Chisel	18	Galvanized	118002	1,000
3/4"	0.048	Chisel	18	Galvanized	118034	1,000
5/8"	0.048	Chisel	18	Galvanized	118058	1,000
1-1/2"	0.048	Chisel	18	Galvanized	118112	1,000
1-1/4"	0.048	Chisel	18	Galvanized	118114	1,000
1-3/4"	0.048	Chisel	18	Galvanized	118134	1,000
1"	0.048	Chisel	18	Galvanized	950001	3,000
2"	0.048	Chisel	18	Galvanized	950002	3,000
3/4"	0.048	Chisel	18	Galvanized	950034	6,000
1-1/2"	0.048	Chisel	18	Galvanized	950112	3,000
1-1/4"	0.048	Chisel	18	Galvanized	950114	3,000
1-3/4"	0.048	Chisel	18	Galvanized	950134	3,000

- Approved for use in all pressure treated lumber such as ACQ and MCQ
- Polymer coating on nail head reduces staining and streaking by 80% compared to traditional hot dipped galvanized nails
- IRC R319.3 code approved for use in pressure treated lumber in accordance with ASTM A 153





18 GAUGE FINISH NAILS FOR USE WITH



P18-200 -18 GAUGE BRAD NAILER



P18-FS200 -18 GAUGE BRAD NAILER/STAPLER



IMLI200 - 18 GAUGE FINISH NAILER

OOL ACCESSORIES



Part No. 403720

Pneumatic Oil



Part No. 219090

Pneumatic Oil w/ Antifreeze



Part No. 650039

Universal Trim Fuel Cell (4 Pk)



N18-125 1-1/4" Narrow Soffit Stapler

Adjustable Exhaust

- Maintains a
Cleaner Working
Environment

INCLUDES

N18-125 - 1-1/4" Narrow Soffit Stapler

Safety glasses

Carrying case

Owner's manual

TOOL ACCESSORIES





Pneumatic Oil



Part No. 219090

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-125 - 1-1/4" Narrow Soffit Stapler—

POWERFUL – MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.

POWERFUL EASY ACCESS PROFESSIONAL

ADVANTAGES

- Ergonomically Balanced and Lightweight —
 To reduce arm fatigue.
- Quick Clear Nose Piece to reduce down time on the job if a jam should occur.
- Narrow Nose Piece Allows the tool to fit into tight corners.
- Magnesium Metal Housing Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK	
1/2"	' 1/4" Chisel		18	Galvanized	180121	1,000	
3/4"	3/4" 1/4" Chisel		18	Galvanized	180341	1,000	
1"	1/4"	Chisel	18	Galvanized	180011	1,000	
1"	1/4" Chisel		18	Galvanized	140015	5,000	
1-1/4"	1/4"	Chisel	18	Galvanized	181141	1,000	
1-1/4"	1/4"	Chisel	18	Galvanized	141145	5,000	

[•] Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-125

Weight: 2.5 lbs

Height: 9"

Length: 9-1/4"

Nail Capacity: 100

Nail Range: 3/4" - 1-1/4"

Nail Type: GSN 18, 3/16 inch (1/4" crown)

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.







1-1/2" Narrow Crown Finish Stapler

Ergonomically Balanced and Lightweight – To Reduce Arm Fatigue





INCLUDES

N18-150 — 1-1/2" Narrow Crown Finish Stapler

Safety glasses

Carrying case

Owner's manual

TOOL ACCESSORIES







Part No. 219090

Oil Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-150 - 1-1/2" Narrow Crown Finish Stapler—

POWERFUL - MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.

POWERFUL



PRECISE



PROFESSIONAL



ADVANTAGES

- Adjustable Exhaust Maintains a cleaner working environment.
- Quick Clear Nose Piece to reduce down time on the job if a jam should occur.
- Narrow Nose Piece Allows the tool to fit into tight corners.
- Magnesium Metal Housing Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1/2"	1/4"	Chisel	18	Galvanized	180121	1,000
3/4"	1" 1/4" Chisel 18	18	Galvanized	180341	1,000	
1"	1/4"	Chisel	18	Galvanized	180011	1,000
1"	1/4"	Chisel	18	Galvanized	140015	5,000
1 1/4"	1/4"	Chisel	18	Galvanized	181141	1,000
1 1/4"	1/4"	Chisel	18	Galvanized	141145	5,000
1 1/2"	1/4"	Chisel	18	Galvanized	141125	5,000

[•] Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-150

Weight: 2.8 lbs

Height: 9-3/4"

Length: 11-1/2" Nail Capacity: 100

Nail Range: 3/4" - 1-1/2"

Nail Type: GSN 18, 3/16 inch (1/4" crown)

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.







US-100 Upholstery/ Craft Stapler

Easy-load Magazine



DESCRIPTION/SUGGESTED SPECIFICATIONS

US-100 Upholstery/Craft Stapler—

LONG NARROW NOSEPIECE FOR TIGHT SPOTS

Lightweight - At only 2 lbs this tool is very easy to handle and decreases operator fatigue. Heavy-duty driver blade.

FAST PRECISE QUICK LOAD

TO THE PRECISE QUICK LOAD

ADVANTAGES

■ Drives 3/8" - 9/16" upholstery staples.

Fast - Shoots 5 staples per second

SELECTION CHART

22 Gauge Upholstery Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
3/8"	3/8"	Chisel	22	Galvanized	422038	4,000

• Code approved for use in pressure treated lumber in accordance with ASTM A 153

INCLUDES

US100 Upholstery/Craft Stapler

APPLICATIONS



Upholstery

Crafts

Light paneling

Home project applications

TOOL ACCESSORIES



Pneumatic Oil



Part No. 219090

Pneumatic Oil w/ Antifreeze

SPECIFICATIONS

Part No. US-100

Weight: 2.8 lbs

Height: 9-1/2"

Length: 12-1/2"

Nail Capacity: 100

Nail Range: 3/8" - 9/16"

Nail Type: 22 Gauge Upholstery

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts,

1-year limited on housing and cap parts. For full warranty details, visit

https://paslode.ca/warranty/



HP100 Headless Pin Nailer



DESCRIPTION/SUGGESTED SPECIFICATIONS

HP100 Headless Pin Nailer—

COMPACT – LIGHTWEIGHT.

Multi-directional exhaust port. Pin nails leave a very small hole for easy finishing and painting.

FAST LIGHTWEIGHT PROFESSIONAL

ADVANTAGES

Quick release nose piece

Drives 1/2" to 1-1/2" pin nails

SELECTION CHART

23 Gauge Pin Nails

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1"	0.025	Chisel	23	Brite	323001	3,000
3/4"	0.025 Chisel		23	Brite	323034	3,000
1-1/2"	0.025	Chisel	23	Brite	323112	3,000
1-3/8"	0.025	Chisel	23	Brite	323138	3,000

[•] Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Fine woodworking and trim work

INCLUDES

HP100 Headless Pin Nailer

Safety glasses

Tool case

Allen wrench and oil

TOOL ACCESSORIES



Pneumatic Oil



Part No. 219090

Pneumatic Oil w/ Antifreeze

SPECIFICATIONS

Part No. HP100

Weight: 1.2 lbs

Height: 9-1/4"

11eigiit. 3-1/4

Length: 7-3/4"

Nail Capacity: 100

Nail Range: 1/2" - 1-1/2"

Magazine Angle: Straight

Nail Type: 23 Gauge - Smooth,

Galvanized Pin Nails

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.







Positive Placement PF250S

Dependable, Lightweight, Compact and Accurate



APPLICATIONS



Joist Hangers

INCLUDES

Positive Placement PF250S Safety Glasses

Owner's Manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

Positive Placement Tool—

DESIGNED FOR PROFESSIONAL FRAMERS

Paslode is proud to introduce the latest customer-backed innovation. The Paslode® 21Ž2″ Positive Placement® Metal Connecting System is designed to provide installers the optimal way for fastening structural hardware to wood structures. The pneumatic system significantly reduces installation time, allowing jobs to be completed faster and reducing the need for additional labour.

POWERFUL



FAST

DEPENDABLE



ADVANTAGES

- Versatile: Drives 1 ½" and 2 ½" nails.
- Dependable: Drive nails consistently to maximize productivity and efficiency.
- Lightweight and Compact: Reduces fatigue and increases maneuverability.
- Accurate: Probing tip guides nails into hardware holes.

SELECTION CHART

30 Degree Positive Placement Nails

	LENGTH	SHANK SHANK DIAMETER		DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK
[1-1/2"	0.148	Smooth	30	Galvanized	650014	3,000
	1-1/2"	-1/2" 0.148 Smooth		30	Brite	650646	1,000
	2-1/2"	0.148	Smooth	30	Brite	650027	2,500

- Mechanically Galvanized, premium corrosion protection with code recognition. Recognized for use in ACQ, MCQ and all pressure treated lumber.
- Heat Treated nails to improve drive performance and reduce bending
- ICC-ES Recognized, ESR-2126, ESR-3326, Galvanization meets ASTM B695 Class 55
- Patented Paper Tape Collation formula provides clean shear for consistent drive performance. Maintains Strip integrity when in contact with moisture and will not fall apart when dropped

SPECIFICATIONS

Part No. 511800

Weight: 7.8 lbs

Height: 14"

Length:17.4"

Nail Capacity: 55-60 Nails (2 strips)

Nail Range: .131" to .162" (Shank)

Magazine Angle: 30 Degrees

Nail Type: 1-1/2" to 2-1/2" Positive Placement

Hanger Nails - Brite and Galvanized

Air req: 80-120 PSI

Warranty: 90-day limited on wear parts, 1-year limited on magazine parts, 5-year

limited on housing and cap parts





FloorMaster Plus™

Floormaster Plus™ 2 in 1 Flooring Nailer/Stapler



DESCRIPTION/SUGGESTED SPECIFICATIONS

2 in 1 Flooring Nailer/Stapler—

THE PROFESSIONAL GRADE 2 IN 1 FLOORING TOOL.

Optimal performance and solid reliability. Easy maintenance and low cost of ownership. Lightweight – 10.4 lbs







ADVANTAGES

- Easy Actuation
 - Only 4 lbs of pressure anywhere on poppet valve
 - Compact all-around striking surface to avoid marking/damaging walls
- Industry-Best Design & Ergonomics
 - Reverse handle with foam grip for reduced fatigue
 - Compact size for nailing boards closer to the end walls

SELECTION CHART

Flooring Staples and Cleats

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK	NAILS PER BOX
1-3/4"	Staple	Chisel	15	Brite	151134	1,000	5,000
2"	Staple	Chisel	15	Brite	151002	1,000	5,000
2"	Cleat	Cleat	16	Brite	100002	1,000	

[•] Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS







INCLUDES

Tool & Mallet

SPECIFICATIONS

Part No. F2N1-200

Weight: 10.4 lbs

Height: 18"

Length: 16"

Flooring Fasteners: 15GA staples &

16GA L-cleats

Fastener Lengths: 1-3/4", 2" 15GA staples & 2" 16 GA L-cleats



FloorMaster Pro[™]

Floormaster Pro™ Nailer/Stapler 2 in 1 Combo





INCLUDES

Tool & Mallet

DESCRIPTION/SUGGESTED SPECIFICATIONS

Nailer/Stapler 2 in 1 Combo—

THE PROFESSIONAL GRADE 2 IN 1 FLOORING TOOL.

Optimal performance, unfailing reliability. Ideal for flooring professionals, small contractors and self-employed installers.

PRECISE	SPEED	POWERFUL
Ψ		

ADVANTAGES

- Easy firing pneumatic valve
- Long lasting valve inside
- Light impact all-around striking cap
- Requires only a few drops of non-detergent oil weekly for lubrication

SELECTION CHART

Flooring Staples and Cleats

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK	NAILS PER BOX
1-3/4"	Staple	Chisel	15	Brite	151134	1,000	5,000
2"	Staple	Chisel	15	Brite	151002	1,000	5,000
2"	Cleat	Cleat	16	Brite	100002	1,000	

[•] Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS

1/2" to 3/4" Solid and Engineered Flooring





SPECIFICATIONS

Part No. FNS-200

Weight: 11 lbs

Height: 21-5/8"

Length: 18"

Flooring Fasteners: 15-1/2ga staples

& 16ga L-Cleats

Fastener Lengths: 2", 1-3/4", 1-1/2"







Miscellaneous Fasteners

SELECTION CHART

MISCELLANEOUS FASTENERS

18 Gauge Flooring Cleats									
LENGTH	ТҮРЕ	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	CLEATS PER PACK			
2"	Cleat	Chisel	18	Brite	150018	1,000			
15 Degree Coil Nails									
LENGTH	SHANK DIAMETER	SHANK	DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK			
2"	0.099	Spiral	15	Brite	404582	4,500			
2-1/4"	0.099	Spiral	15	Brite	404583	4,500			
2-1/2"	0.099	Spiral	15	Brite	404584	4,500			
3"	0.12	Spiral	15	Brite	404508	4,500			
3-1/4"	0.12	Spiral	15	Brite	404510	4,500			
18 Gauge GEN-ER-X 7/32" Crown Staples									
LENGTH	ТҮРЕ	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK			
5/8"	7/32"	Chisel	18	Galvanized	732058	5,000			
1"	7/32"	Chisel	18	Galvanized	732001	5,000			
1-3/8"	7/32"	Chisel	18	Galvanized	732138	5,000			

Notes

Notes			



Notes		

TW Construction Products*

National Headquarters

120 Travail Road Markham, Ontario, L3S 3J1

Tel: 905-471-7403 800-387-9692

Fax: 905-471-7208 800-668-8688

Technical and Customer Service Support

Tel: 800-387-9692

Fax: 800-668-8688

Regional Warehouses

- Markham, Ontario
- Coquitlam, British Columbia
- Calgary, Alberta

Ramset, T4, T3, T3Cup, Trakfast, GypFast, Mastershot, Triggershot, Hammershot, PowerPoint, TE Pin and Climacoat are trademarks of Illinois Tools Works, Inc.

A7+, C6+, Dynabolt, G5, Hammer-Set, LDT, Multi-Set II, Poly Set, Red Head, Redi-Drive, S7, Striker, and Trubolt are trademarks of ITW Red Head and Illinois Tool Works, Inc.

Teks, TruGrip GT, Scots, Maxiseal, Dek-Cap, Tapcon,SG, Tapcon, Maxi-Set Tapcon, Condrive, E-Z Ancor, E-Z Toggle, Twist-N-Lock, E-Z Lite, E-Z Mini, Stud Solver, Hi-Lo, S-12, Backer-On, Rock-On, DecKing, Dec-U-Drive, Dek-Cap, Grid-Mate, Grid-Mate, PB, Climaseal, Spex, Climacoat, UltraShield, Climashield and Building Ideas That Work are trademarks of ITW Buildex and Illinois Tool Works. Inc.

Sammy X-Press, Sammy X-Press It, Sammy X-Press Swivel, Sammy X-Press Sidewinder, Tapcon, Sammy Saddle, Speedy Pole Tool, Spot-Rite Level, and Truss-T Hanger are trademarks of ITW Buildex and Illinois Tool Works, Inc.

The term "Paslode" is a trademark and the Paslode logo and all related product and service names, designs and slogans are Paslode trademarks. Paslode, RounDrive, Impulse, Positive Placement are registered trademarks, PowerFramer and quicklode are trademarks of Illinois Tool Works.

R4, RSS, Kameleon, Fin/Trim, RT Composite, Low Profile Cabinet, Pheinox, Top Star, VWS, Caliburn, and The GRK Fasteners Canada Ltd. and all associated designs and logos are trademarks of GRK Fasteners Canada Ltd., used under license.

Hilti is a registered trademark of Hilti, Corp.

DensGlass is a registered trademark of Georgia Pacific Building Products.

Dekstrip, Dektite, Retrofit Dektite, and Dektite are registered trademarks of Deks Industries Pty Ltd. Phillips Square-driv is a registered trademark of the Phillips Screw Company.

© 2022 Illinois Tool Works, Inc. Form. No.02/22

Take Advantage of these Contractor Services from ITW Construction Products Canada

From job sites to engineering firms, from Safety Seminars to on-site services, we hope you take advantage of our many contractor services—at no charge! After all, it's one thing to offer the quality products you need to do your job. It's another to provide you with superior service, engineering expertise and total product support.

At ITW Construction Products Canada, we are proud of the partnerships we have built through the years with our distributor network and contractors. Thanks to quality products, innovative services and on-time delivery, we will continue to build new relationships and strengthen existing ones today... and into the next century.

- Factory representatives with years of training and service experience will go out to your job site to provide you with product, service and technical assistance.
- We provide architects and engineers with complete submittal packages which gives them the technical data needed to specify ITW Construction Products Canada products. Contact your ITW Construction Products Canada Distributor or your nearest Customer Service location to request submittal packages.

Technical Application Assistance:

Our staff of application specialists are ready to assist you with any type of application or code approval question during any phase of your project. Call 1-800-387-9692 between 8:00 a.m. and 5:00 p.m. EST, Monday through Friday.

Distributed By

The information and recommendations in this document are based on the best information

The information and recommendations in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this document.